



**2010-11 Arctic Cat F8/Sno Pro Single Pipe
131-137 Polished Ceramic**

Installation Instructions

Remove stock pipe; be sure to keep all stock springs. If you have a ceramic coated pipe there is no need to remove the stock heat shields. If you are installing a black satin pipe and installing the heat shields, remove off factory pipe and re-install on Straightline single. Factory covers do not fit the best; this may take some work, to produce the power the pipe sizes and lengths needed to be changed.

Be sure the Straightline single has no manufacture defects. If the pipe has been run/used there are **no warrantees** for fitment.

Jetting Requirements

Straightline has seen in testing no need for a fuel programmer, but we still recommend the customer to check his own jetting on the new pipe.

Peak rpm – Peak hp increase 8100

Clutching - Straightline recommends adding a clutch kit to operate at the new recommended hp rpm. Straightline kit part number is. 124-144

Quantity	Item #	Descriptions	In Box
1	131-137	Pipe	
1		Sticker	

Checked and Packaged By

Straightline Performance 15250 Hornsby St Forest Lake, MN 55025 651-466-0212

www.straightlineperformance.com

Technical questions please email tech@straightlineperformance.com



Facebook @ straightlineperformanceinc

Youtube @ straightlineperfinc

Twitter @ straightlineperf