

Polaris Boost RMK 850 Straightline Performance Off-Trail "Boondocking" Performance Clutch Kit (0-3000ft) SKU# 123-161

Parts included in Clutch Kit:

1-Primary Spring 123-100 (Green)
1- P22 Clutch Weight Kit (123-169)
1-Secondary Spring 125-129 (black/white)
1-TSS-04 Helix 125-132
1 - 460079K (rollers for Secondary)

## Settings:

Helix Setting - Side B


Total Clutch Weight (84.7 +/- .5) <u>Clutch weight starting point:</u> Base Hole – 3.3g Total 1 – Short Bolt 1.2g 1 – Tungsten Washer 2.1g Center Hole — 6 g Total 1 – Long Bolt 1.8g 2 - Tungsten Washers 2.1g

Tip Hole – 2.4 g Total 1 – Long Bolt 1.8g 2 - Steel Washers .3g

See Clutch Weight Box for overview on weights/washers/bolts and tungsten.

Operating RPM:

Operating RPM - 8350-8500



Remove the primary clutch and install the weights and primary spring.

Remove secondary clutch and install new rollers, helix, and spring in proper setting.

Inspect all internal clutch components for wear. **If excesses** wear is prevalent replace needed items.

Check out Straightline @ www.straightlineperformance.com

Tech questions can be handled via e-mail at tech@straightlineperformance.com

